

OIL ABSORBENT-BIODESTRUCTOR AridGrow PHOA-M (4-8 g/g)



PROPERTIES:

- ✓ The standard absorption capacity for oil is 4 g/g, light oil products 8 g/g. It is operational in a wide temperature range from ±50°C.
- ✓ The rate of absorption of oil products at a temperature of +20°C is: commercial oil of medium viscosity 15-30 sec, gasoline and thin (rainbow) films of hydrocarbon nature from the water surface 1-2 sec, motor oil 5-8 sec. At negative temperatures, the oil absorption time increases to 1-2 min.
 structure of the absorbent.
 ✓ DOESN'T REQUIRE SPECIAL COLLECTING & ANY DISPOSAL of the used absorbent, BECAUSE of the used absorbent in the particles in encapsulated form
- ✓ It has water-repellent properties, is not wetted by water and does not dissolve in water, providing buoyancy for at least 25 days. Nontoxic, explosion and fire safe.
- Environmentally safe for people, animals and plants, does not contain harmful chemical elements and waste products.
- ✓ It has no restrictions on use and is approved by sanitary authorities of all countries as a natural substance that does not require hygienic regulations.
- ✓ STORAGE CONDITIONS: Keep in a dry da±rk place at a temperature ±50°C, avoiding direct sunlight and high humidity. The shelf life and storage IN UNBROKEN ORIGINAL FACTORY PACKAGING IS NOTLIMITED.

APPLICATION ON SOIL & WATER SURFACES:

- Spread OIL ABSORBENT on a surface of an oil-polluted area by any appropriate method. Wait a bit and there is NO MORE ANY ECOLOGICAL THREAT, i.e. contamination encapsulates within the absorbent particles without any opportunity to go out. Also you can use any special eqiupment (air or sand blaster machinery) for powerful immobilization of the contaminant into the capillary structure of the absorbent.
- COLLECTING & ANY DISPOSAL of the used absorbent, BECAUSE OF keeping contaminant within the particles in encapsulated form without any opportunity to go out, where is gradual COMPLETE BIODEGRADATION INTO WATER (H2O) & CARBON DIOXIDE (CO2) goes naturally in an environmentally friendly way at the molecular level NO LONGER THAN FOR 1 YEAR. It can be used further as ameliorant soil-conditioner for.
- ✓ USED ABSORBENT with absorbed any oil products belongs to hazard class 4 - low-hazard substances, according to GOST 12.1.007, and can be disposed of as ordinary household waste.

MANUFACTURER'S RECOMMENDATIONS FOR APPLICATION OIL ABSORBNT-BIODESTRUCTOR AridGrow® PHOA-M

TR BY 490421644.010-2023

AridGrow PHOA-M (Powdered Humic Oil Absorbent - Multifunctional) is a natural, environmentally friendly absorbent substance, which is a powdered concentrate of Humic Substances isolated from Peat by using special AridGrow® Technology. Highly versatile tool for removing thin film of oil and oil products on various land & water surfaces. Surface Cleaner for oiled steel. transport equipment, breakwaters, piers, ramps and other surfaces contaminated with petroleum products and non-polar hydrocarbons. Highly effective for rapid absorption and fixation of petroleum, oil, fuel oil and other liquid non-polar organic pollutants by hydrocarbon nature.

APPLIED FOR: express fixation, absorption & environmental recovery of any oil-polluted areas on land & water surface, removing thin iridescent oil films, cleaning ports, piers, breakwaters and transport equipment, surface oiled metal structures, bridges, oil tanks and greasy production facilities of automotive service and fuel stations, etc.

IN EMERGENCY SITUATIONS to liquidate the consequences of accidents during production and transportation of any kind of hydrocarbons in the oil wells and offshore platforms, oil and fuel lines, tank farms and fuel depots, oil transfer stations, road and rail tankers, gas stations, etc.

PRODUCED in 20kg/501 PP bags with HDPE liner. Packaging meets international requirements for this type of product for easy calculation of the requied amount of absorbent for the customer: 1 bag absorbs 1 barrel (160 liters) of crude oil or 200 liters of light hydrocarbon pollutants or completely restores the area contaminated with oil products at the rate of $\pm 1 \, \text{kg} / 1 \, \text{sq.m.}$, depending on the depth of penetration of the pollutant.

RATE OF OIL PRODUCT SORPTION: commercial oil of medium viscosity at a temperature of +20C is 15-30 sec, gasoline and thin (rainbow) films of hydrocarbon nature from the water surface 1-2 sec, motor oil 5-8 sec. At negative temperatures, the oil absorption time increases from several minutes to several hours.

ANY COLLECTION AND SPECIAL DISPOSAL of the conglomerate (the products of interaction of the sorbent with oil and oil products) is NOT **REQUIRED** and is performed at the request of the consumer, since the oil and oil products absorbed by the sorbent no longer pose an environmental threat and are contained inside the sorbent particles in an encapsulated form, where their gradual COMPLETE BIODEGRADATION INTO WATER (H,O) AND CARBON DIOXIDE (CO2) OCCURS NATURALLY AT THE MOLECULAR LEVEL OVER A PERIOD OF UP TO 1 YEAR without the possibility of reverse desorption and are classified as low-hazard preparations of hazard class 4, according to GOST 12.1.007-76.



Desert Gardening Technology AridGrow® and its Products!

AridGrow® Product is Powdered Humic Oil Absorbent-Biodestructor of a Quick-Effect and highly concentrated Natural Product, processed from Peat by special AridGrow Technology with the purpose of modifying its physical and chemical properties and qualities for consumer demands and designed for express-fixation, absorption and encapsulation of all types of hydrocarbon pollutants inside its structure without the possibility of reverse desorption, where their gradual COMPLETE BIODEGRADATION INTO WATER (H,O) AND CARBON DIOXIDE (CO2) occurs in a natural way at the molecular level over a period of UP TO 1 YEAR. Subsequently, after the completion of the hydrocarbon biodegradation process, it continues to act as ameliorant soil-conditioner to restore degraded soils disturbed by human economic activity with the possibility of their subsequent involvement in economic circulation.

> ABSORBENT-BIODESTRUCTOR AridGrow®PHOA-M in 400kg/1cub.m. PP big-bag

ABSORBENT-BIODESTRUCTOR AridGrow®PHOA-M in 20kg/50L PP bag with HDPE liner





AridGrow Products are developed by the Institute for Nature Management of the National Academy of Sciences of Belarus with scientific-technical support of the UK scientificresearch company «AridGrow Laboratories LTD» and passed successful comprehensive tests during 15 years in the Middle East. Recommended to use by the Ministry of Natural Resources and Environmental Protection of the Republic of Belarus and the Regional Office for the Near East and North Africa of the Food and Agriculture Organization of the United Nations.

CERTIFIED IN EUROPEAN UNION FOR ORGANIC FARMING.

Made in Belarus by Belarus-UK joint venture «AridGrow Production JLLC» under the license and control of the UK scientific-research company «AridGrow Laboratories LTD».



For buying AridGrow® Products contact, please: BELARUS-UK JLLC "ARIDGROW PRODUCTION" Chervonoe 31-1, Zhitkovichi District, Gomel Region Tel: +375 (29) 369-00-99 | Fax: +375 (17) 369-00-99 More details at: www.aridgrow.by | www.aridgrow.international

